



86

Morris & Perry (Gurney Slade Quarries) Ltd  
Gurney Slade Quarry, Gurney Slade, Radstock, Somerset BA3 4TE

**13**  
Certificate No. 0086-CPD-594473

**EN 13108-1**  
**Asphalt Concrete for roads and other trafficked areas**  
AC 32 HDM bin LS 40/60  
Gurney Slade Quarry Asphalt Plant, Radstock  
Benninghoven Travelmix 2000 Asphalt Plant  
Mix Code: M53

**General requirements + fundamental requirements**

Void content

- maximum
- minimum

$V_{\max NR}$

$V_{\min NR}$

Water sensitivity

$ITSR_{NR}$

Resistance to abrasion by studded tyres

$ABR_{NR}$

Reaction to fire

Euroclass Cfl<sub>NR</sub>

Temperature of the mixture

40/60 Pen

160°C to 190°C

Grading (passing)

40mm sieve

100%

31,5mm sieve

99%

20mm sieve

86%

6,3mm sieve

52%

2mm sieve

33%

0,250mm sieve

11%

0,063mm sieve

8,0%

Binder content

B<sub>min</sub> 4,4%

4,6%

Stiffness

- minimum
- maximum

$S_{\min NR}$

$S_{\max NR}$

Resistance to permanent deformation

$f_{\max NR}$

**Valid from :** 01/09/2017

**Issued :** 11/09/2017